



## > SEMI-ROTARY MANUAL PUMP




### AT2

 FRENCH MANUFACTURE

#### USE :

Manual pump equipped for the transfer of fluids in a potentially explosive atmosphere.

The product complies with the ATEX 94/9/CE standard.

Pump marking : CE  II 2 GD IIC T4 (Tf<120°C).

#### COMPATIBLE FLUIDS :

Water, petrol, gasoil, alcohol, toluene, trichlorethylene, acetone, white spirit, etc.

#### COMPONENTS :

Body, lid and lever : Cast iron (EN-GJL-200 or 250).

Internal mechanism : Brass (Cu Zn39 Pb1 Al B).

Couplings : Ø 1" Cast iron (EN-GJL-200).

Pump axle and screws : Steel (11SMNBP37).

Seat gasket : polytetrafluorethylene braid (PTFE).

Coupling gasket : PEB (Expanded PTFE).

Fixed to a support by 2 M12 screws. dist. betw. centres 142 mm.

Filter : 300 microns, 304 stainless steel rose (Z6 CN 18.19).

Cable length 2 m with clamp for earthing.

#### SEALING OF THE SHAFT :

PTFE braid held by a cast iron compression gland.

#### TECHNICAL CHARACTERISTICS :

WEIGHT	8,5 kg
HOURLY FLOW	2000 liters/H
FLOW RATE - DOUBLE STROKE	80 per mn
TOTAL LIFT HEIGHT	15 m

SEALING CONTROL WITH COMPRESSED AIR	5 kg/cm <sup>2</sup>
INTAKE CAPACITY	7 m
FLOW BY DOUBLE STROKE	0,41 liter
ANGULAR TRAVEL OF THE LEVER	115°

#### SIZE :

